



# mmWave G

MMW, high frequency, low loss, glass reinforced PCB base material

## FEATURES

- Stable Dk/Df over frequency and temperature.
- Low dielectric tolerance +/-0.04.
- Low Moisture Absorption
- UL 94 V-0 flame rating.

## APPLICATIONS

Automotive radar applications  
 Base Station Antenna  
 Cellular telecommunications system  
 Global positioning satellite antennas  
 Direct broadcast satellites

## GENERAL PROPERTIES

Test Items	Test Method	Test Condition	Direction	Unit	Typical Value
Dielectric Constant (Process Dk)	IPC-TM-650 2.5.5.5	10GHz/23°C	Z	-	3.15
Dielectric Constant (Process Dk)	IPC-TM-650 2.5.5.15	10GHz/23°C	Z	-	3.16
Dielectric Constant (Design Dk)	Resonator Ring	77GHz/23°C	Z	-	3.18
Dissipation Factor, Df	IPC-TM-650 2.5.5.5	10GHz/23°C	Z	-	0.002
Dissipation Factor, Df	IPC-TM-650 2.5.5.15	10GHz/23°C	Z	-	0.002
Tg	IPC-TM-650 2.4.24.4	DMA	-	°C	200
Td	ASTM D3850	TGA	-	°C	395
Coefficient of Thermal Expansion (50°C-150°C)	IPC-TM-650 2.4.41	TMA 25°C, 50%RH	X	ppm/°C	20
			Y	ppm/°C	20
			Z	ppm/°C	40
Volume Resistivity	IPC-TM-650 2.5.17.1	A	-	MΩ-cm	1.32X10 <sup>11</sup>
Surface Resistivity	IPC-TM-650 2.5.17.1	A	-	MΩ	1.04X10 <sup>11</sup>
Peel Strength	IPC-TM-650 2.4.8	after solder float HOz HVLP foil	-	N/mm [lb/in]	0.60 [3.73]
Water Absorption	IPC-TM-650 2.6.2.1	-	-	%	0.06
Thermal Conductivity	ASTM D5470	50°C	Z	W/m·K	0.40
Density	ASTM D792	A	-	g/cm <sup>3</sup>	1.52
Flammability	UL94	-	-	Rating	V-0

### Remarks:

All the typical values listed above are for your reference only and not intended for specification. Please contact Shengyi Technology Co., Ltd. for detailed information. All rights from this data sheet are reserved by Shengyi Technology Co., Ltd.



# mmWave G

MMW, high frequency, low loss, glass reinforced PCB base material

## Product Specification

STANDARD THICKNESS	STANDARD PANEL SIZE	COPPER FOIL
0.004" (0.102mm)	18"×24" (457mm×610mm) 21"×24" (534mm×610mm)	1/2 Oz (18 μ m) HVLP copper foil. 1 Oz (35 μ m) HVLP copper foil.
0.005" (0.127mm)		
0.010" (0.254mm)		
0.020" (0.508mm)		
0.030" (0.762mm)		